ALGANET



BASIC SOLUTION FOR THE REMOVAL OF MOSSES AND LICHENS



YIELD

The yield varies from 2 to 20 m² of surface with 1 kg of product.

ALWAYS CARRY OUT TESTS BEFORE USE

Anyone, before use, needs to know the characteristics of our products by reading the label affixed to each package, the technical data sheet and the safety data sheet compliant with Regulation (EC) 1272/2008 (CLP) (and subsequent amendments and adjustments) and of Regulation (EU) 2015/830, or eventually by contacting us directly. However, we recommend to strictly follow the instructions given or received.

We also recommend to carry out a preventive sampling to detect any unexpected results with respect to the method of application or the quality of the result. Keep the package well sealed and out of the reach of children. Aerate the working environment well during and also after the application of the product.

Do not eat or drink when using this product.

DESCRIPTION

Water soluble product for the removal of mosses, molds and blackening due to lichen incrustations, absorbed by materials stones due to persistent moisture or to exposure situations unfavorable: shady areas, tall and shady plants, relevant exposure to rainwater. ALGANET acts effectively on any type of material without damaging or staining the treated surface. The product totally eliminates the residues of fresh or encrusted mosses from time, not only on the surface but also in depth as it is possible to penetrate the support by making sure to bring back the surface to its original appearance. Thanks to its balanced formulation it is possible to apply ALGANET on any type of support: marble, granite, beole, sandstone, volcanic stone, slate, terracotta, agglomerated cement, exposed cement, white and colored plasters, etc. It is the ideal product for the field of external maintenance of stable, floor and wall coverings.

APPLICATION

ALGANET is applied by spray or brush directly on the parts to be cleaned or cleaned as is or diluted in water according to the type of surface and the amount of substance to be removed. It can be applied indifferently on dry or wet surfaces without any difference in the result, let the product for at least 30 minutes then rinse to remove any residues. In the case of non-optimal results it is recommended to repeat the operation. ALGANET does not damage the surfaces even if left to act for longer hours. Dilution:

- · Ordinary cleaning: dilute 1 part product with 1 part water (1:1)
- Intense cleaning: apply the pure product directly on the surface to be cleaned.

RECOMMENDATIONS

Avoid direct contact with plant organisms. After the treatment carry out a thorough washing, we recommend the use of CIBERMAC detergent diluted in 10% water. The product is aggressive in contact with the skin, it is recommended to wear protective clothing and take off, if necessary, those wet by the product. The product cannot stand freezing, store it in well-closed and well-protected places, at a temperature not lower than 10 °C.

NOTE

Our indications and technical advice, both given by voice or in writing, refer to our personal best knowledge and do not include any guarantee against third parties.

We kindly invite you to adapt our products to your needs and working conditions: methods of use and processing techniques are exclusively under the responsibility of the buyer.

As far as we are concerned, we guarantee constant quality in our supplies within our general conditions of sale. Should you verify our liability for any type of damage, the liability is limited solely and exclusively to the value of the goods supplied by us and used by you.