

SOLVENT BASED CONSOLIDANT



DESCRIPTION

BE 53 is a mixture of resins in solvent made to obtain a consolidation action of old stone surfaces, sandstone and limestone, brick, marble in general, laid both internally and externally.

The application of our product allows, thanks to the action of solvents, an accentuated penetration into the materials on which it comes employee and a subsequent strong consolidation action due to the characteristics of the resins present in it.

BE 53's action is carried out by preventing or limiting significantly dusting and chalking and, in extreme cases, blocking the flaking of the stone supports caused by the absorption of moisture and rain. Our product penetrates deeply into the damaged support until reaching the part that is still intact, thus recomposing the stone mass.

The supports treated with BE 53 will return to have a good consistency, also the stone surface will assume characteristics of impermeability to water and moisture.

YIELD

The yield varies from 3 to 10 m² of surface with 1 L of product.

- Very absorbent surfaces: 3-6 m²/L
- Low absorbent surfaces: 6-10 m²/L

APPLICATION

Apply BE 53 on well cleaned and dry surfaces, by spray or brush, taking care to well uniformize the product and avoiding dripping. The product must be applied until the support is saturated in several coats at a distance of 30/40 minutes from each other. The product is ready to use.

Do not apply on wet supports or at temperatures below 10 °C.

ALWAYS CARRY OUT TESTS BEFORE USE

Anyone, before use, needs to know the characteristics of our products by reading the label affixed to each package, the technical data sheet and the safety data sheet compliant with Regulation (EC) 1272/2008 (CLP) (and subsequent amendments and adjustments) and of Regulation (EU) 2015/830, or eventually by contacting us directly. However, we recommend to strictly follow the instructions given or received.

We also recommend to carry out a preventive sampling to detect any unexpected results with respect to the method of application or the quality of the result. Keep the package well sealed and out of the reach of children. Aerate the working environment well during and also after the application of the product.

Do not eat or drink when using this product.

RECOMMENDATIONS

For supports with limited absorbency, dilute the product with SOLV X up to 50%.

The product cannot stand freezing, store it in well-closed and well-protected places, at a temperature not lower than 10 °C. Always protect yourself with mask, gloves and protective clothing.

NOTE

Our indications and technical advice, both given by voice or in writing, refer to our personal best knowledge and do not include any guarantee against third parties.

We kindly invite you to adapt our products to your needs and working conditions: methods of use and processing techniques are exclusively under the responsibility of the buyer.

As far as we are concerned, we guarantee constant quality in our supplies within our general conditions of sale. Should you verify our liability for any type of damage, the liability is limited solely and exclusively to the value of the goods supplied by us and used by you.