

BEM 126

WATER-BASED CONSOLIDANT



DESCRIPTION

BEM 126 is a water-based resin mixture made to obtain an action of protection and consolidation of old surfaces in sandstone, brick and concrete agglomerates, marble, laid inside or outside. The application of our product allows you to obtain, thanks to penetration into the supports on which it is used, an excellent consolidation action and good abrasion protection. The action of BEM 126 takes place by forming a slight physical barrier, which significantly limits dusting and chalking and, in cases extreme, blocks the flaking of stone supports caused by the absorption of moisture and rain.

The supports treated with BEM 126 will return to having a good consistency, furthermore the stone surface will take on characteristics of impermeability to water and moisture, excellent resistance to trampling dirty and dirt absorption.

BEM 126 can be used as a finishing product on interior and outdoor rough floors, ideal for industrial quartz floors and it can also be used with floor washing machines.

YIELD

The yield varies from 4 to 30 m² of surface with 1 L of product.

- Very absorbent surfaces: 4-12 m²/L
- Medium absorbent surfaces: 12-20 m²/L
- Low absorbent surfaces: 20-30 m²/L

APPLICATION

Apply BEM 126 on well cleaned and possibly dry surfaces, spreading it out with a cloth or with a roller, taking care to uniform it avoiding dripping, or by spraying; the product must be applied until the support is saturated. BEM 126 is ready to use.

During the application, we recommend you to remove any product accumulations from the surface before the complete drying. When used as a finishing product, it can be diluted in water up to 25% (one part product and three parts water).

BEM 126 can be applied on industrial quartz floors, as a stopper, dustproof, anti-dirt, it leaves the surface with satin finish and it is washable with washer-dryers machines.

ALWAYS CARRY OUT TESTS BEFORE USE

Anyone, before use, needs to know the characteristics of our products by reading the label affixed to each package, the technical data sheet and the safety data sheet compliant with Regulation (EC) 1272/2008 (CLP) (and subsequent amendments and adjustments) and of Regulation (EU) 2015/830, or eventually by contacting us directly. However, we recommend to strictly follow the instructions given or received.

We also recommend to carry out a preventive sampling to detect any unexpected results with respect to the method of application or the quality of the result. Keep the package well sealed and out of the reach of children. Aerate the working environment well during and also after the application of the product.

Do not eat or drink when using this product.

RECOMMENDATIONS

The product cannot stand freezing, store it in well-closed and well-protected places, at a temperature not lower than 10 °C. Always protect yourself with mask, gloves and protective clothing.

NOTE

Our indications and technical advice, both given by voice or in writing, refer to our personal best knowledge and do not include any guarantee against third parties.

We kindly invite you to adapt our products to your needs and working conditions: methods of use and processing techniques are exclusively under the responsibility of the buyer.

As far as we are concerned, we guarantee constant quality in our supplies within our general conditions of sale. Should you verify our liability for any type of damage, the liability is limited solely and exclusively to the value of the goods supplied by us and used by you.