

## WATER-BASED WATER-OIL REPELLENT ANTI-STAIN PROTECTIVE TREATMENT WITH WET EFFECT



### YIELD

The yield varies from 4 to 30 m<sup>2</sup> of surface with 1 L of product. Below we indicate some finishes and their respective yields:

- Sandblasted / Bush-hammered / Flamed: 4-6 m<sup>2</sup>/L
- Matt polished: 7-15 m<sup>2</sup>/L
- Glossy: 30 m<sup>2</sup>/L

### ALWAYS CARRY OUT TESTS BEFORE USE

Anyone, before use, needs to know the characteristics of our products by reading the label affixed to each package, the technical data sheet and the safety data sheet compliant with Regulation (EC) 1272/2008 (CLP) (and subsequent amendments and adjustments) and of Regulation (EU) 2015/830, or eventually by contacting us directly. However, we recommend to strictly follow the instructions given or received.

We also recommend to carry out a preventive sampling to detect any unexpected results with respect to the method of application or the quality of the result. Keep the package well sealed and out of the reach of children. Aerate the working environment well during and also after the application of the product. Do not eat or drink when using this product.

### DESCRIPTION

CS 51 WET is an anti-stain product with a wet effect, based on water, suitable for the protection of stone and terracotta surfaces. The presence in the formulation of small amounts of solvents compatible with water makes it suitable for application on supports that still have traces of moisture inside them, without that this renders the application ineffective.

The formulation of CS 51 WET is the result of years of experience in the treatment of stone surfaces that allowed us to obtain an ideal product for professional use since, in addition to maintaining the characteristics protection of solvent-based products this product, for its compatibility with water, allows to significantly reduce the times of intervention and the relative costs, just think of the dead times caused by waiting for the surfaces to dry after washing, before treatment.

Despite its characteristics of total compatibility with water, it is recommended not to apply it on supports excessively wet, which while not nullifying the effectiveness of the treatment, would make it less valid over the time. If an overlap with products is required, finishing based on waxes or water-based resin, will not occur problems of any kind. The product can be applied on marble, granite, beole, sandstone, volcanic stones, agglomerated of cement and grit, standard and rustic/artisan terracotta, basalts, which can be used to obtain flooring rather than coverings, facades, ventilated walls, etc.

### APPLICATION

CS 51 WET can be applied with normal treatment methods such as those by brush, spray, roller, cloth, in lines of production, rather than personal methods honed by professionals in their operational experiences that also vary depending on the type support and finish you want to obtain. We indicate below, based on our experience, the types of application to be carried out on a series of finishes:

- MATT POLISHED with cloth
- SANDBLASTED - BUSH HAMMERED by brush or spray
- FLAMED by roller, by spray

### RECOMMENDATIONS

Wait at least 12 hours before applying a second coat. The product cannot stand freezing, store it in well-closed and well-protected places, at a temperature not lower than 10 °C. Always protect yourself with mask, gloves and protective clothing.

### NOTE

Our indications and technical advice, both given by voice or in writing, refer to our personal best knowledge and do not include any guarantee against third parties.

We kindly invite you to adapt our products to your needs and working conditions: methods of use and processing techniques are exclusively under the responsibility of the buyer.

As far as we are concerned, we guarantee constant quality in our supplies within our general conditions of sale. Should you verify our liability for any type of damage, the liability is limited solely and exclusively to the value of the goods supplied by us and used by you.