

SOLVENT-BASED, NEUTRAL, WATER-OIL REPELLENT ANTI-STAIN PROTECTIVE FOR ROUGH/ABSORBENT SURFACES



DESCRIPTION

MAX is a neutral, solvent-based, water-oil repellent, breathable, non-filming, fully absorbed protective. It is the ideal product for any type of rough surface, indoor and outdoor.

Our product does not change the aesthetic appearance of the surfaces on which it is applied, it does not create surface films, it resists UV rays, it is ideal for the protection of floors, stairs, shelves and window sills with various finishes such as: bush-hammered, sandblasted, split, flamed and any other type of rough finish, as well as antiqued marble tumbled.

The product does not alter the degree of slipperiness of the support.

The types of material that can be treated are the most varied: marble, granite, limestone, lava stone, basalt, sandstone, beola, slate, grits, agglomerates in general, marble-resin, quartz-resin, porphyry, slate, colored cement, tuff stones, quartzite.

YIELD

The yield varies from 5 to 12 m² of surface with 1 L of product.

* Product certificated for safe food contact

ALWAYS CARRY OUT TESTS BEFORE USE

Anyone, before use, needs to know the characteristics of our products by reading the label affixed to each package, the technical data sheet and the safety data sheet compliant with Regulation (EC) 1272/2008 (CLP) (and subsequent amendments and adjustments) and of Regulation (EU) 2015/830, or eventually by contacting us directly. However, we recommend to strictly follow the instructions given or received.

We also recommend to carry out a preventive sampling to detect any unexpected results with respect to the method of application or the quality of the result. Keep the package well sealed and out of the reach of children. Aerate the working environment well during and also after the application of the product.

Do not eat or drink when using this product.

APPLICATION

MAX can be applied, on clean and dry surfaces, by roller, brush, spray or with a cotton cloth. Apply one or two times depending on the surface to protect (example: for flat surfaces we suggest to apply it twice, while for vertical surfaces one time is enough).

Below there are some finishes and their respective yields:

- Sandblasted 4 - 6 m²/L
- Split 4 - 6 m²/L
- Flamed 4 - 6 m²/L
- Bush-hammered 4 - 6 m²/L
- Matt and polished 12 - 20 m²/L
- Slates 10 - 20 m²/L

RECOMMENDATIONS

The product cannot stand freezing, store it in well-closed and well-protected places, at a temperature not lower than 10 °C. Always protect yourself with mask, gloves and protective clothing.

NOTE

Our indications and technical advice, both given by voice or in writing, refer to our personal best knowledge and do not include any guarantee against third parties.

We kindly invite you to adapt our products to your needs and working conditions: methods of use and processing techniques are exclusively under the responsibility of the buyer.

As far as we are concerned, we guarantee constant quality in our supplies within our general conditions of sale. Should you verify our liability for any type of damage, the liability is limited solely and exclusively to the value of the goods supplied by us and used by you.