

# PLATINUM



**SOLVENT-BASED, NEUTRAL, WATER-OIL REPELLENT, ANTI-STAIN PROTECTIVE**

## DESCRIPTION



High quality product that represents the synthesis of our knowledge regarding the use of the best raw materials currently on the market and their use in formulations refined through daily use on construction sites, in Italy and abroad, by our specialized staff. Being a highly professional product, it is particularly suitable for professionals in the sector and specifically for companies operating in the field of protective treatments. PLATINUM is the universal protective, odorless, guaranteed for all surfaces. In fact, it is suitable to be applied on floors, walls, kitchen tops, stairs, bathroom tops, exterior walls, interior walls, tables, shelves and any other type of stone material worked. Properties: neutral, non-filming, non-yellowing, breathable, odorless, reversible, resistant to U.V.A. rays, acid rain. It protects against smog, atmospheric dirt, trampling dirt, food-grade stains (such as oil, coffee, etc.), writing and scribbles made with markers or spray cans on facades. It has limited resistance to acidic substances and it prevents the formation of mosses, lichens (therefore it has the function of limiting the formation of the bacterial flora that would nestle between the interstices of the stone material in the natural state). It also provides a barrier against stains and oxidations caused by rising humidity or impurities present in the laying mixtures or substrates. Where to apply: PLATINUM is applied with excellent results on marble, granite, gneiss, slate, sandstone, quartzite, lava stone, trachyte, resin agglomerates, cement agglomerates, Venetian stucco, Venetian terrazzo, terracotta, colored cement, cement. Surface finishes to be treated: glossy, polished, brushed.

## YIELD

**The yield varies from 3 to 40 m<sup>2</sup> of surface with 1 L of product.**

- Very porous surfaces: 3-6 m<sup>2</sup>/L
- Medium porous surfaces: 7-15 m<sup>2</sup>/L
- Low porous surfaces: 20-30 m<sup>2</sup>/L
- Very compact surfaces: 30-40 m<sup>2</sup>/L

**\* Product certificated for safe food contact**

## ALWAYS CARRY OUT TESTS BEFORE USE

Anyone, before use, needs to know the characteristics of our products by reading the label affixed to each package, the technical data sheet and the safety data sheet compliant with Regulation (EC) 1272/2008 (CLP) (and subsequent amendments and adjustments) and of Regulation (EU) 2015/830, or eventually by contacting us directly. However, we recommend to strictly follow the instructions given or received.

We also recommend to carry out a preventive sampling to detect any unexpected results with respect to the method of application or the quality of the result. Keep the package well sealed and out of the reach of children. Aerate the working environment well during and also after the application of the product.

Do not eat or drink when using this product.

## APPLICATION

PLATINUM is applied by roller, brush, spray with low pressure pump, by hand with a cotton cloth, taking care to spread it evenly and without leaving surpluses, any product accumulations can still be easily removed with a suitable solvent. The product does not change the aesthetic appearance of the support on which it is applied. For split, sandblasted and bush-hammered surfaces, we recommend a spray application with a low pressure pump.

## RECOMMENDATIONS

For cleaning avoid the use of products containing solvents and pure alcohol. The product cannot stand freezing, store it in well-closed and well-protected places, at a temperature not lower than 10 °C. Always protect yourself with mask, gloves and protective clothing.

## NOTE

Our indications and technical advice, both given by voice or in writing, refer to our personal best knowledge and do not include any guarantee against third parties.

We kindly invite you to adapt our products to your needs and working conditions: methods of use and processing techniques are exclusively under the responsibility of the buyer.

As far as we are concerned, we guarantee constant quality in our supplies within our general conditions of sale. Should you verify our liability for any type of damage, the liability is limited solely and exclusively to the value of the goods supplied by us and used by you.