

# PLATINUM ZIP



SOLVENT-BASED, ANTI-STAIN, TONING PROTECTIVE WITH HIGH RESISTANCE



## DESCRIPTION

PLATINUM ZIP can be applied with excellent results on marble, granite, gneiss, sandstone, quartzite, lava stone, porphyry, slate, trachyte, limestone, of various origins, colors and conformation, with glossy, polished, brushed finish.

Indoor and outdoor use. Ideal for floorings, kitchen tops, and bathroom tops. New and old installation surfaces. Ideal for restoring the original color of the stone.

High-quality water-oil repellent protective with reviving effect in solvent solution, with characteristics of very high resistance to U.V.A. rays, acid rain, washing with common detergents and solvents. It has excellent resistance to acid substances and protects against graffiti. Breathable, non-yellowing and reversible through the use of a specific product, PLATINUM ZIP is the ideal product for the toning treatment of shiny, brushed and polished surfaces. It highlights the natural colors of the stone material and, in addition to giving an absolute brilliance, it perfectly seals the micro-cracks and natural porosities present in the stone materials. The formulation allows its use on all types of materials, laid both inside and outside, with different finishes and absorbency. Ideal for finishing slabs in the processing lines or of the products in the marble workshops.

## YIELD

The yield varies from 3 to 40 m<sup>2</sup> of surface with 1 L of product.

- Very porous surfaces: 3-6 m<sup>2</sup>/L
- Medium porous surfaces: 7-15 m<sup>2</sup>/L
- Low porous surfaces: 20-30 m<sup>2</sup>/L
- Very compact surfaces: 30-40 m<sup>2</sup>/L

\* Product certified for safe food contact

## ALWAYS CARRY OUT TESTS BEFORE USE

Anyone, before use, needs to know the characteristics of our products by reading the label affixed to each package, the technical data sheet and the safety data sheet compliant with Regulation (EC) 1272/2008 (CLP) (and subsequent amendments and adjustments) and of Regulation (EU) 2015/830, or eventually by contacting us directly. However, we recommend to strictly follow the instructions given or received.

We also recommend to carry out a preventive sampling to detect any unexpected results with respect to the method of application or the quality of the result. Keep the package well sealed and out of the reach of children. Aerate the working environment well during and also after the application of the product.

Do not eat or drink when using this product.

## APPLICATION

**Manual use:** apply PLATINUM ZIP on clean and dry surfaces by brush, cotton cloth, roller, spray, evenly, wait about 30/45 minutes to allow a total absorption of the product. Then, remove any surplus with dry cotton or appropriate felt. For less absorbent surfaces, apply the product carefully and do not exceed the quantities.

**Use in the production line - using waxing machines:** pour PLATINUM ZIP into the appropriate dosing trays. Then, adjust the dripping according to the type of stone and absorbency. Distribute it on the slab by means of spreader brushes which the automatic system is equipped with by carrying out a subsequent removal of any surplus with appropriate felts. The drying of the absorbed product will be complete after 36/48 hours.

## RECOMMENDATIONS

It is always advisable to test the product on a little visible area and check the real absorbency of the support. For routine maintenance it is recommended to use the neutral detergent CIBERNET. For old laying surfaces, wash with CIBERMAT before applying the product. The product cannot stand freezing, store it in closed and well protected places at a temperature not lower than 10°C. Always protect yourself with mask, gloves and protective clothing.

## NOTE

Our indications and technical advice, both given by voice or in writing, refer to our personal best knowledge and do not include any guarantee against third parties.

We kindly invite you to adapt our products to your needs and working conditions: methods of use and processing techniques are exclusively under the responsibility of the buyer.

As far as we are concerned, we guarantee constant quality in our supplies within our general conditions of sale. Should you verify our liability for any type of damage, the liability is limited solely and exclusively to the value of the goods supplied by us and used by you.