

WATER-BASED PRE-GROUTING TREATMENT



DESCRIPTION

PRESIGIL is a water-based protective formulation, suitable to prevent the penetration of cement-based compounds and epoxy sealants on marble, granite, gneiss, quartzite, volcanic stone, slate, sandstone and split stone in general, with all types of finishing, terracotta, cement tiles, agglomerates of cement. The product is also suitable for use on particularly absorbent terracotta surfaces such as rustic terracotta. The treatment is to be applied before the sealing of the floors or coverings, it protects against any construction site dirt, it facilitates the removal of the residues of sealant as it does not allow the penetration into the superficial porosity of the surfaces, it is very effective even in the presence of sealants additived with oxides of strong colors. PRESIGIL can be applied on wet surfaces and it allows to carry out the treatment without waiting for the drying times of the supports. It is applied on surfaces placed both inside and outside and it does not require maintenance.

YIELD

The yield varies from 8 to 15 m² of surface with 1 L of product.

- Absorbent surfaces: 8-10 m²/L
- Low-absorbent surfaces: 10-15 m²/L

APPLICATION

Apply a coat of PRESIGIL by spraying uniformly; on very absorbent surfaces apply two coats at a distance of 3-4 hours. The product will be able to carry out its protective action not earlier than 8-12 hours from the application. The removal of sealant residues and construction site dirt in general can be carried out using CIBERMAC and repeating, if necessary, the washing in the case of more tenacious residues. Cleaning with CIBERMAC also causes the almost total removal of the treatment with PRESIGIL; therefore, it will be necessary to provide a final protective treatment by means of specific products for the various types of surface and depending on the desired effect.

ALWAYS CARRY OUT TESTS BEFORE USE

Anyone, before use, needs to know the characteristics of our products by reading the label affixed to each package, the technical data sheet and the safety data sheet compliant with Regulation (EC) 1272/2008 (CLP) (and subsequent amendments and adjustments) and of Regulation (EU) 2015/830, or eventually by contacting us directly. However, we recommend to strictly follow the instructions given or received.

We also recommend to carry out a preventive sampling to detect any unexpected results with respect to the method of application or the quality of the result. Keep the package well sealed and out of the reach of children. Aerate the working environment well during and also after the application of the product. Do not eat or drink when using this product.

RECOMMENDATIONS

Before applying PRESIGIL take care to remove any residues of construction site and excess dusty residues. The product cannot stand freezing, store it in well-closed and well-protected places, at a temperature not lower than 10 °C. Always protect yourself with suitable means of personal protection, especially for eyes and hands.

NOTE

Our indications and technical advice, both given by voice or in writing, refer to our personal best knowledge and do not include any guarantee against third parties.

We kindly invite you to adapt our products to your needs and working conditions: methods of use and processing techniques are exclusively under the responsibility of the buyer.

As far as we are concerned, we guarantee constant quality in our supplies within our general conditions of sale. Should you verify our liability for any type of damage, the liability is limited solely and exclusively to the value of the goods supplied by us and used by you.