

STAIN REMOVER - EXTRACTOR OF GREASY AND OILY SPOTS



DESCRIPTION

SMACOIL consists of a mixture of solvents and fillers absorbents suitable for the removal of oil and grease stains from surfaces such as: floors, coverings, furnishing elements, stairs in marble, granite, sandstone, quartzite, concrete agglomerates, terracotta.

With SMACOIL you get a quick elimination of stains fresh even with a single application; for old stains or repeated applications are required.

Thanks to its effectiveness and versatility, SMACOIL removes stains absorbed by motor oil from industrial floors and split stones.

It is very effective to remove dark halos and stains caused by silicone products in cartridges.

YIELD

It is not possible to indicate the yield as there could be various problems you could face.

APPLICATION

Before applying the SMACOIL product, clean the part to be stained in order to remove oily residues present on the surface by application of CIBERMAC diluted in 10% water.

When the area is dry, apply SMACOIL as indicated: energetically shake the bottle for homogenize the product contained, then pour on the stain to remove the quantity necessary to cover it completely; leave SMACOIL act for about three hours and then remove the residue dry with a damp cloth. Repeat the operation if necessary until the stain is completely removed. Apply on all surfaces and with any type of finish.

ALWAYS CARRY OUT TESTS BEFORE USE

Anyone, before use, needs to know the characteristics of our products by reading the label affixed to each package, the technical data sheet and the safety data sheet compliant with Regulation (EC) 1272/2008 (CLP) (and subsequent amendments and adjustments) and of Regulation (EU) 2015/830, or eventually by contacting us directly. However, we recommend to strictly follow the instructions given or received.

We also recommend to carry out a preventive sampling to detect any unexpected results with respect to the method of application or the quality of the result. Keep the package well sealed and out of the reach of children. Aerate the working environment well during and also after the application of the product.

Do not eat or drink when using this product.

RECOMMENDATIONS

The product cannot stand freezing, store it in well-closed and well-protected places, at a temperature not lower than 10 °C. Always protect yourself with mask, gloves and protective clothing.

NOTE

Our indications and technical advice, both given by voice or in writing, refer to our personal best knowledge and do not include any guarantee against third parties.

We kindly invite you to adapt our products to your needs and working conditions: methods of use and processing techniques are exclusively under the responsibility of the buyer.

As far as we are concerned, we guarantee constant quality in our supplies within our general conditions of sale. Should you verify our liability for any type of damage, the liability is limited solely and exclusively to the value of the goods supplied by us and used by you.