

## SOLVENT-BASED, ODOURLESS, NEUTRAL, WATER-OIL REPELLENT STAIN PROTECTION FOR SURFACES WITH LOW ABSORBENCY



### YIELD

The yield varies from 6 to 40 m<sup>2</sup> of surface with 1 L of product.

- BUSH-HAMMERED: 6-8 m<sup>2</sup>/L
- BRUSHED: 15-20 m<sup>2</sup>/L
- HONED: 10-12 m<sup>2</sup>/L
- POLISHED: 20-40 m<sup>2</sup>/L

\* Product certificated for safe food contact

### ALWAYS CARRY OUT TESTS BEFORE USE

Anyone, before use, needs to know the characteristics of our products by reading the label affixed to each package, the technical data sheet and the safety data sheet compliant with Regulation (EC) 1272/2008 (CLP) (and subsequent amendments and adjustments) and of Regulation (EU) 2015/830, or eventually by contacting us directly. However, we recommend to strictly follow the instructions given or received.

We also recommend to carry out a preventive sampling to detect any unexpected results with respect to the method of application or the quality of the result. Keep the package well sealed and out of the reach of children. Aerate the working environment well during and also after the application of the product. Do not eat or drink when using this product.

### DESCRIPTION

STARK is a long lasting, solvent-based, anti-stain and water-oil repellent product. A protective treatment for polished and brushed surfaces.

STARK has the appearance of a transparent liquid with an high penetration, even on very compact surfaces such as polished marble, granites, slates, basalt, porphyry and porcelain stoneware. The product finds its best use in the home furnishing sector where it provides an excellent resistance both against oily stains and also stains that you can daily find on the surfaces of home. STARK also protects against rising humidity and avoids halos and bleaching in humid environments such as pools, saunas and wellness centers, environments with high concentration of water vapor.

The product has a high breathability, if its application is made respecting the recommended instructions; it leaves the support colourless. Only its excess can cause halos, which are easily removable with the use of our product SOLV X.

### APPLICATION

STARK can be applied, on clean and dry surfaces, by roller, brush, spray or with a cotton cloth. Apply one or two times depending on the surface to protect (example: for flat surfaces we suggest to apply it twice, while for vertical surfaces one time is enough).

The surfaces are walkable after 4 from the application but the total cross-linking process is completed after 72 hours. For daily cleaning we suggest our sanitizing detergent CIBERNET.

For cleaning rough surfaces (bush hammered, sandblasted), when dirty, we suggest to clean with CIBERMAC, which can also be used for cleaning before restoring the treatment.

### RECOMMENDATIONS

The product cannot stand freezing, store it in well-closed and well-protected places, at a temperature not lower than 10 °C. Always protect yourself with mask, gloves and protective clothing.

### NOTE:

Our indications and technical advice, both given by voice or in writing, refer to our personal best knowledge and do not include any guarantee against third parties.

We kindly invite you to adapt our products to your needs and working conditions: methods of use and processing techniques are exclusively under the responsibility of the buyer.

As far as we are concerned, we guarantee constant quality in our supplies within our general conditions of sale. Should you verify our liability for any type of damage, the liability is limited solely and exclusively to the value of the goods supplied by us and used by you.