

WS 70

SOLVENT-BASED ANTI-STAIN PRODUCT WITH SATIN WET EFFECT FOR ROUGH/ABSORBENT SURFACES

DESCRIPTION



WS 70 is the ideal product for the treatment of stone materials rough, sandblasted, flamed to which you want to give a finishing effect of wet satin.

The product in addition to highlighting the natural colors of the treated material ensures a perfect seal against the absorption of substances staining and against the aggression of acidic substances contained in food. WS 70 is very effective with just one application thanks to the action of quality materials combined with solvent characterized by quick drying, this feature indicates it as a product ideal for use on light coloured surfaces where it was difficult to obtain a tonalization at the first step; naturally for stone materials the treatment is easier.

WS 70 can be applied on sandblasted, flamed, bush-hammered, split, laid both externally and internally, both flat and vertical. Ideal product for treating tables, shelves, kitchen tops, stairs, floors and walls.

YIELD

The yield varies from 10 to 30 m² of surface with 1 L of product.

APPLICATION

Apply WS 70, evenly, on well cleaned and dry surfaces, with a cotton cloth, a roller, a brush; spread a possible second coat, if necessary, only after the drying of the first application.

- For a light satin wet effect, apply one coat of product.
 - For a strong satin wet effect, apply a second coat after 12/24 hours.
- WS 70 can be applied on any type of absorbent stone material and on agglomerates.

It is recommended to pack the treated pieces after at least 12 hours from treatment; the treated pieces are manageable, for storage, after 2-3 hours.

ALWAYS CARRY OUT TESTS BEFORE USE

Anyone, before use, needs to know the characteristics of our products by reading the label affixed to each package, the technical data sheet and the safety data sheet compliant with Regulation (EC) 1272/2008 (CLP) (and subsequent amendments and adjustments) and of Regulation (EU) 2015/830, or eventually by contacting us directly. However, we recommend to strictly follow the instructions given or received.

We also recommend to carry out a preventive sampling to detect any unexpected results with respect to the method of application or the quality of the result. Keep the package well sealed and out of the reach of children. Aerate the working environment well during and also after the application of the product.

Do not eat or drink when using this product.

RECOMMENDATIONS

For compact or low absorbency surfaces dilute WS 70 with SOLV X at 50%. The product cannot stand freezing, store it in well-closed and well-protected places, at a temperature not lower than 10 °C.

Always protect yourself with mask, gloves and protective clothing.

NOTE

Our indications and technical advice, both given by voice or in writing, refer to our personal best knowledge and do not include any guarantee against third parties.

We kindly invite you to adapt our products to your needs and working conditions: methods of use and processing techniques are exclusively under the responsibility of the buyer.

As far as we are concerned, we guarantee constant quality in our supplies within our general conditions of sale. Should you verify our liability for any type of damage, the liability is limited solely and exclusively to the value of the goods supplied by us and used by you.